Product Data Sheet



ATS8100UP

CD Rom de mise à jour pour le logiciel - TITAN (Multilingual CD-ROM édition)

Product Overview

TITAN provides a simple, open look Windows interface that simplifies the programming of all the Advisor MASTER options.

Up/download

A PC running TITAN can be connected to a control panel either remotely via the built-in PSTN dialer or locally via RS232. The RS232 connection is timed when using the on board RS232 port or permanent when using the optional ATS1801 Computer & Printer interface. Used in either mode, Titan is capable of up and downloading the entire database at once or settings by settings.

TITAN can handle up to 32 COM ports simultaneously with up to 16 ATS control panels on each port (total 512 panels). Each control panel is an independent security system reporting to one TITAN.

Back-up facility

TITAN has a back-up and archiving facility for up to 9999 independent systems on one PC. Each system consists of up to 1024 panels sharing the same user database.

Reports

A powerful report printing facility produces detailed programming sheets for all system information contained within the TITAN database. This feature enables quick reference for trouble shooting, expansion, programming and client administration.

It also features a range of flexible history reports, which can be produced with any combination of date/time ranges, keypads, users or other parameters and the most complicated queries can be achieved.

ATS smart card programming

TITAN, together with the optional card programmer allows users to program cards on-site.



Caractéristiques

- CD de mise à jour
- Avoir la version ATS8100

ATS8100UP

CD Rom de mise à jour pour le logiciel - TITAN (Multilingual CD-ROM édition)

Caractéristiques techniques

Computer Requirements		
	Windows 2000 or XP	
	Pentium 166 or higher	
	32 MB of RAM	
	100 MB of free hard drive space	
	CD-ROM player and mouse	
Max. number of PC with TITAN connected	1 (TITAN is a single user software)	
Max. number of panels sim. in operation	4 x 16	
Max. number of panels in database	9999 systems x 1024 panels/system	
Max. number of printers	Dependant on the number of ports & allocation of those ports	
Communication ports on computer:	Com 1, Com 2, Com 3, Com 4	
Spec. cable with ATS1801	4 core shielded data cable RS232 (not twisted pair)	
Spec. cable with on board RS232 port	ATS1630 active RS232 cable	
Maximum cabling distance on RS232	15 m	
Port A of the interface (computer)	Serial RS232, Tx, Rx, CTS, RTS, GND	
Port B of the interface (printer)	Serial RS232, Tx, CTS, GND	

Comment commander

Référence	Description
ATS8100UP	CD Rom de mise à jour pour le logiciel - TITAN (Multilingual CD-ROM édition)

Remote diagnostics

All ATS control panels can run a diagnostic session upon request of TITAN that uploads the results. The parameters checked by the diagnostic facility are in line with the EN50131 and include the measurement of analogue values like the input loops resistance and the voltage and current supplied to all RAS* and DGP** on the bus.

Graphical maps

Graphic alarm maps (floor plans or pictures) can be configured to provide detailed information about any I/O point in the system. The graphic map displays the I/O point in case of activation and allows the operator to perform manual overrides directly from the map. TITAN implements Point and Click operation with pop up menus for ease of use. All alarm events may be handled from maps rather than the Alarm window.

Multiple operators can use the same TITAN, each having specific access rights and restrictions.

Real time event log

A real-time event log shows all events as they happen with a time and date stamped description of the event, this is then logged to the history database. History can be archived, reported and viewed as a constantly visible window.

Photo ID

TITAN provides a completely integrated video & image solution that enables the production of photo ID cards for users, contractors or visitors. Pictures can be captured from live video or imported in digital format.

TITAN allows designing and printing any kind of card layouts with or without company and user details taken from the database.

