



Fiche Produit

ARD2-XDNP

Caméra dôme anti vandale 1/4" couleur / monochrome 480 lignes, 0,3lux a f1.4

Rugged Dome II

The weatherproof, vandal resistant day/night rugged dome II features a new design of die-cast housing, an impact-resistant Lexan dome, tamperproof screws and a hinged cover for easy setup. A durable gasket on the base of the rugged dome provides a watertight seal to protect the camera. It will withstand temperatures ranging from -10 to 50 °C.



Caractéristiques

- New stylish design
- Weatherproof housing
- Tamperproof screws and a Lexan dome for vandal resistance
- Hinged cover for easy adjustment and setup
- High-resolution Colour/Monochrome camera
- 3.5 to 8mm varifocal Auto Iris lens option
- True Day/Night camera with motorised filter assembly

ARD2-XDNP

Caméra dôme anti vandale 1/4" couleur / monochrome 480 lignes, 0,3lux a f1.4

Caractéristiques techniques

Image sensor

- 1/4 in. interline transfer Sony super HAD CCD

Resolution

- 480 TVL

Sensitivity

- 0.2 lux at F1.4

Pixels (H x V)

- 795 x 596

Scanning system

- 625 lines, 50 fields PAL

S/N ratio

- >48 dB (AGC off) AGC: Max 36 dB

Synchronisation

- Internal/line lock AC (phase adjustable)

Gamma

- 0.45

Video out

- 1 V pk-pk at 75 ohm load

Electronic shutter

- 1/50 - 1/100,000 sec.

Power supply

- 10 to 40 VDC or 18 to 30 VAC

Power consumption

- 3.5 W at 12 VDC

Operating temperature

- -10 to 50°C

Weight

- 820 g

Dimensions (Ø x H)

- 149 x 102 mm

Comment commander

ARD2-XDNP

Caméra dôme anti vandale 1/4" couleur / monochrome
480 lignes, 0,3lux a f1.4, vari-focal 2.8 - 5.8mm, 12vdc 24 Vac

